



PRELOAD(kgf)	~
R.D.	~
S.F. (kgf)	~
DRAG TORQUE(kgf-cm)	~
DIRECTION OF TURN	R
P.C. DIA.	20.2
BALL DIA.	3.175
BACKLASH	0.04MAX
CIRCUIT	4
LEAD ANGLE	4.51
DYNAMIC (kgf)	938
STATIC (kgf)	1993
LEAD	5

SPECR20-5T4-FSI

MAX. AXIAL LOAD(kgf)		LUBRICATION	SPACE BALL	BALL DIA.	3.175
MAX. ROTATIONAL SPEED (rpm)		SPACE BALL		BACKLASH	0.04MAX
DN VALUE		E1 TYPE ASSEMBLY METHOD		CIRCUIT	4
MAX. FEED RATE(m/min)		CUSTOMER DRAWING NO.		LEAD ANGLE	4.51
ACCELERATION (m/sec <sup>2</sup> )		CUSTOMER MC TYPE		DYNAMIC (kgf)	938
SUPPORT METHOD		CUSTOMER AXIAL TYPE		STATIC (kgf)	1993
				LEAD	5

	UNCHAMFERED USE <input type="checkbox"/> C0.5 <input checked="" type="checkbox"/> C1 <input type="checkbox"/> C ROUGH M/C/FIN M/C GRD <input type="checkbox"/> 25a <input checked="" type="checkbox"/> 6.3a <input type="checkbox"/> 0.4a <input type="checkbox"/> 0.4a <input type="checkbox"/> 0.4a SCALE 1: X	MAT. SH: ROLLED DATE 2010.06.22
	NORMAL TOLERANCE mm UP TO 6 30 120 300 600 1200 2400 OVER ±0.1 ±0.2 ±0.3 ±0.4 ±0.5 ±0.8 ±1.0 ±1.5	NT: SNCM220/Equivalent DWG Ford THREAD BALL TRACK APPD Cody HRC 56 ~ 62 PROCESS NO. G
HIWIN® BALLSCREWS		CUSTR HIWIN DWG.NO.

\*BREAK SHARP EDGE UNLESS OTHER SPECIFIED.  
 \*未量倒角者去毛邊 (C0.2MAX)  
 ● THREAD END ALLOWS ABOVE LENGTH OUT OF HARDNESS TOLERANCE.

DATE	MODIFICATION	APPROVED
------	--------------	----------

\* PLEASE IGNORE CHINESE CHARACTERS WHICH ARE FOR OUR REFERENCE ONLY.