



PRELOAD(N)	~
R.D	~
S.F (N)	~
DRAG TORQUE (Nm)	~
DIRECTION OF TURN	R
PC DIA.	34.26
BALL DIA.	6.35
BACKLASH	~
CIRCUIT	5
LEAD ANGLE	5.31
DYNAMIC (kN)	~
STATIC (kN)	~
LEAD	10

SPEC: R32-10K5-FSC

MAX. AXIAL LOAD(kN)		LUBRICATION		BALL DIA.	6.35
MAX. ROTATIONAL SPEED (rpm)		SPACE BALL		BACKLASH	~
DN VALUE		EI TYPE ASSEMBLY METHOD		CIRCUIT	5
MAX. FEED RATE(m/min)		CUSTOMER DRAWING NO.		LEAD ANGLE	5.31
ACCELERATION (m/sec ²)		CUSTOMER MC TYPE		DYNAMIC (kN)	~
SUPPORT METHOD		CUSTOMER AXIAL TYPE		STATIC (kN)	~
				LEAD	10

UNCHAMFERED USE R0.5 R1 R
 ROUNG M/C/FIN M/C/ GRD M/C/ SCALE
 25g 6.3g 0.4g 1: X
 UNTOL DIMN mm
 UP TO 6 30 120 300 600 1200 2400 OVER
 ±0.1 ±0.2 ±0.3 ±0.4 ±0.5 ±0.8 ±1.0 ±1.5
 E300: ~
 HIWIN® BALLSCREWS
 MATA SH: ROLLED DATE 2007.06.28
 NT: SNCM220/SCM415 DWG KAI
 THREAD BALL TRACK APPD Lady
 HRC 56 ~ 62 PROCESS NO. G
 CUSTR HIWIN
 DWG.NO.

*BREAK SHARP EDGE UNLESS OTHER SPECIFIED.
 *未畫倒角者以R0.5MAX
 ● THREAD END ALLOWS ABOVE LENGTH OUT OF HARDNESS TOLERANCE.

DATE	MODIFICATION	APPROVED
------	--------------	----------

* PLEASE IGNORE CHINESE CHARACTERS WHICH ARE FOR OUR REFERENCE ONLY.