



SPEC: R40-5K6-FSC

MAX. AXIAL LOAD (kgf)	LUBRICATION	PRELOAD (kgf)	~
MAX. ROTATIONAL SPEED (rpm)	SPACE BALL	R.D.	~
DN VALUE	EI TYPE ASSEMBLY METHOD	S.F. (kgf)	~
MAX. FEED RATE (m/min)	CUSTOMER DRAWING NO.	DRAG TORQUE (kgf-cm)	~
ACCELERATION (m/sec ²)	CUSTOMER MC TYPE	DIRECTION OF TURN	R
SUPPORT METHOD	CUSTOMER AXIAL	P.C. DIA.	40.03
		BALL DIA.	3.175
		BACKLASH	0.04MAX
		CIRCUIT	6
		LEAD ANGLE	2.28
		DYNAMIC (kgf)	2590
		STATIC (kgf)	10060
		LEAD	5

UNCHAMFERED USE <input type="checkbox"/> CO.5 <input checked="" type="checkbox"/> C1 <input type="checkbox"/> C	SCALE	MAT. SH: ROLLED	DATE	2010.06.02
ROUGH M/C/FIN M/C/GRD <input type="checkbox"/> 25a <input type="checkbox"/> 6.3a <input type="checkbox"/> 0.4a <input type="checkbox"/> 0.2a	1: X	NT: SNCM220/Equivalent	DWG	Rita
NORMAL TOLERANCE mm		THREAD BALL TRACK APPD	Lady	
UP TO 6 30 120 300 600 1200 2400 OVER		HRC 56 ~ 62	PROCESS NO.	G
±0.1 ±0.2 ±0.3 ±0.4 ±0.5 ±0.8 ±1.0 ±1.5		CUSTR	HIWIN	
THREAD LENGTH		DWG.NO.		

*BREAK SHARP EDGE UNLESS OTHER SPECIFIED.
*未查銳角者去毛邊 (CO.2MAX)
● THREAD END ALLOWS ABOVE LENGTH OUT OF HARDNESS TOLERANCE.

* PLEASE IGNORE CHINESE CHARACTERS WHICH ARE FOR OUR REFERENCE ONLY.

DATE	MODIFICATION	APPROVED